

# HOW TO ORDER

## Filter Regulator – B08-B38

Filter/Regulator Numbering System

**B 1 8 – 0 3 – F H G P**

**B Unit Function**

B = Filter/Regulator Combination

**1 Family**

**8** 08 = Miniature

18 = Compact

28 = Standard

38 = Jumbo (Not all configurations available for the B38 Series Filter/Regulator Refer to price list.)

**0 Thread Type**

0 = NPT

C = BSPP (ISO, R228 [G Series])

**3 Pipe Size**

1 = 1/8                      4 = 1/2

2 = 1/4                      6 = 3/4

3 = 3/8                      8 = 1

**F Filter/Regulator Combination**

Diaphragm Function	Fluorocarbon	Spring Range			
		0-30 psi (0-2,1 Bar)	0-60 psi (0-4,1 Bar)	0-125 psi (0-8,5 Bar)	0-250 psi (0-17 Bar)
Relieving	No	C	D	F	G
	Yes	J	K	L	M
Non-relieving	No	P	Q	R	S
	Yes	V	X	Y	Z

**H Bowls/Drains**

Drains	Plastic w/guard Nitrile Standard	Metal w/sight glass <sup>1</sup> Fluorocarbon Standard
None	C	D
Std Auto Drain <sup>2</sup>	G	H
Manual Drain	K	L
Low Flow Auto Drain <sup>2</sup>	N	P
Piston Drain (B08 only)	R	S

<sup>1</sup>B08 Filter/Regulator has an all metal bowl (no sight gauge)

<sup>2</sup>Except 08 Series

**G Options**

- 0 = None
- E = Bar Gauge (Except 38 Model)
- C = Tamper Resistant Regulator Adj (Tamper kit not installed. Kit is shipped loose in carton)
- G = Pressure Gauge
- P = Metal Panel Nut (Except 38 Model)

**P Options**

- 0 = None
- E = Bar Gauge (Except 38 Model)
- C = Tamper Resistant Regulator Adj (Tamper kit not installed. Kit is shipped loose in carton)
- G = Pressure Gauge
- P = Metal Panel Nut (Except 38 Model)
- K = Pressure Gauge mounted on back side (B08 only)

*Note: When selecting from the options columns, please enter letters in alphabetical order, for example:*

**B18 – 03 – F H G P**

**"F" Series Filters, Type "A" 5 micron elements**

All Wilkerson Type "A" 5 micron elements meet or exceed ISO Class 3 for maximum particle size and concentration of solid contaminants.

**Note:** All classes above refer to International Standards Organisation (ISO) standard 8573-1:1991 (E), pertaining to maximum particle size and concentration of solid contaminants, and maximum oil content.