

HOW TO ORDER FRL Combinations – C18

| Model Type | Port Size | Plastic Bowl/ Bowl Guard with Gauge 0-125 psi (8,6 bar) | Plastic Bowl/ Bowl Guard without Gauge 0-125 psi (8,6 bar) | Metal Bowl/ Sight Gauge with Gauge 0-150 psi (8,6 bar) | Metal Bowl Sight Gauge without Gauge 0-125 psi (8,6 bar) | Plastic Bowl/Bowl Guard/Gauge with End Blocks 3-60 psi (0,2-4, 1 bar) |
|----------------------------------|-----------|---|--|--|--|---|
| Manual Drain | 1/4 | C18-C2-FKG0 | C18-C2-FK00 | C18-C2-FLG0 | C18-C2-FL00 | C18-C2-FKGB |
| | 3/8 | C18-C3-FKG0 | C18-C3-FK00 | C18-C3-FLG0 | C18-C3-FL00 | C18-C3-FKGB |
| | 1/2 | C18-C4-FKG0 | C18-C4-FK00 | C18-C4-FLG0 | C18-C4-FL00 | C18-C4-FKGB |
| Automatic Mechanical Drain | 1/4 | C18-C2-FGG0 | C18-C2-FG00 | C18-C2-FHG0 | C18-C2-FH00 | C18-C2-FGBG |
| | 3/8 | C18-C3-FGG0 | C18-C3-FG00 | C18-C3-FHG0 | C18-C3-FH00 | C18-C3-FGBG |
| | 1/2 | C18-C4-FGG0 | C18-C4-FG00 | C18-C4-FHG0 | C18-C4-FH00 | C18-C4-FGBG |

