

## HOW TO ORDER FRL Combinations – C08

| Model Type    | Port Size | Plastic Bowl/<br>Bowl Guard<br>Manual Drain<br>without Gauge<br>0-125 psi<br>(0-8,6 bar) | Plastic Bowl/<br>Bowl Guard<br>Manual Drain<br>with Gauge<br>0-125 psi<br>(0-8,6 bar) | Metal Bowl/<br>Manual Drain<br>without Gauge<br>0-150 psi<br>(0-8,2 bar) | Metal Bowl/<br>Manual Drain<br>with Gauge<br>0-125 psi<br>(0-8,6 bar) |
|---------------|-----------|--|---|--|---|
| Relieving     | 1/8       | C08-C1-FK00  | C08-C1-FKG0   | C08-C1-FL00  | C08-C1-FLG0   |
|               | 1/4       | C08-C2-FK00  | C08-C2-FKG0   | C08-C2-FL00  | C08-C2-FLG0   |
| Non-Relieving | 1/8       | C08-C1-RK00  | C08-C1-RKG0   | C08-C1-RL00  | C08-C1-RLG0   |
|               | 1/4       | C08-C2-RK00  | C08-C2-RKG0   | C08-C2-RL00  | C08-C2-RLG0   |

